

## Kongres Container

# 650w solar panel specifications



## Overview

---

Electrical Specifications□\*STC : Irradiance 1000w/ m<sup>2</sup>,AM1.5 spectrum,  
module temperature 25°CPeak power (Pmax): 650wCell Efficiency:  
20.9%Maximum power voltage (Vmp):37.68VMaximum power current (Imp):  
17.26AOpen circuit voltage (Voc): 45.49VShort circuit current (Isc):  
18.32APower.

Electrical Specifications□\*STC : Irradiance 1000w/ m<sup>2</sup>,AM1.5 spectrum,  
module temperature 25°CPeak power (Pmax): 650wCell Efficiency:  
20.9%Maximum power voltage (Vmp):37.68VMaximum power current (Imp):  
17.26AOpen circuit voltage (Voc): 45.49VShort circuit current (Isc):  
18.32APower.

650W panels deliver exceptional space efficiency: With efficiency ratings between 20.8% and 22.5%, these panels generate nearly double the power of standard residential panels while requiring only 50-60% more roof space, making them ideal for space-constrained installations. Installation complexity.

The SS- (650-670)-66MDH-G12, developed by Sunova Solar, is an [ . ]  
Introducing the 210 Series XP- (640~670)-66BDG solar panel by XPOWER [ . ]  
Introducing the EVO6 SE6-66HBD 650-670W by SUNEVO, a cutting-edge [ . ]  
Introducing the MSM640-660S-D66, an extraordinary solar panel [ . ] The.

Note: Your Enquiry will be sent directly to Trina Solar Co., Ltd. Trina Solar Co., Ltd. Solar Panel Series Vertex TSM-DE21 650-675W. Detailed profile including pictures, certification details and manufacturer PDF .

El Solar panel 650w Aiko N Type It is designed with the innovative technology of ABC Back Contact to maximize solar collection. Contains 144 cells. Editorial Board El Solar Panel 650W Aiko N Type It is one of the most advanced and efficient options available in the current photovoltaic market.

Specifications included in this datasheet are subject to change without notice. LONGi reserves the right of final interpretation.(20241118 BGV02 Draft) .

\*Bifacial Gain: The additional gain from the back side compared to the power

of the front side at the standard test condition. It depends on the mounting (structure, height, tilt angle, etc.) and albedo of the ground. 36.5 kg Max. Ø 25 mm at 23 m/s 2400 Pa or 244 kg/m<sup>2</sup> 5400 Pa or 550 kg/m<sup>2</sup> Temp.

## 650w solar panel specifications

---

## Contact Us

---

For catalog requests, pricing, or partnerships, please visit:  
<https://drugiswiatowykongrespolakow.pl>